

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

**(19) World Intellectual Property
Organization
International Bureau**



(43) International Publication Date
17 June 2004 (17.06.2004)


PCT

(10) International Publication Number
WO 2004/051882 A1

- (51) International Patent Classification⁷: **H04B 7/06, 7/08**
- (21) International Application Number: **PCT/IB2003/005056**
- (22) International Filing Date: **10 November 2003 (10.11.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data: **60/431,124 4 December 2002 (04.12.2002) US**
- (71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).**
- (71) Applicant (for AE only): **U.S. PHILIPS CORPORATION [US/US]; 1251 Avenue of the Americas, New York, NY 10510-8001 (US).**
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **VAN HOUTUM, Wim [NL/NL]; P.O. Box 220, NL-5600 AE Eindhoven (NL).**
- (74) Common Representative: **RONINKLIJKE PHILIPS ELECTRONICS N.V.; c/o YORKS, Brinton, W., Jr., 22100 Bothell Everett Highway, Bothell, OH 98021 (US).**
- (81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.**
- (84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**
- Published: **— with international search report**

[Continued on next page]

(54) Title: DELAY DIVERSITY IN A WIRELESS COMMUNICATION SYSTEM



(57) Abstract: A wireless communication system for voice or data such as a WLAN system utilizes multiple transmit antennae and multiple receive antennae. The multiple transmit antennae exhibit different delay paths and the multiple receive antennae exhibit different delay paths. The delay of one of the transmit antennae paths is different from a delay of one of the receive antennae paths. In a preferred embodiment one of the transmit antenna paths uses a non-zero value delay component of a value which differs from the value of a non-zero value delay component of one of the receive antenna paths.

WO 2004/051882 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.